

# cloud



The new

## CTP50

Faster and Easier

- Faster Printing Speeds
- Paper Jam-Free Auto Cutter
- Comprehensive Barcode Formats
- Low Power Consumption and Paper Saving
- Supports Various Options and Interfaces



## INTERFACE VIEW



▲ USB Only




▲ USB + RS-232(9Pin + RJ45)



▲ USB + RS-232(25Pin)



▲ USB + Parallel



▲ USB + RS-232(RJ45) + Ethernet (3-Combo)



▲ USB + Wi-Fi(WLAN)

## KEY FEATURE



Easy paper loading & Jam Free/Apply auto cutter



Aluminum main frame structure with low noise & robustness



Easy assembly and disassembly with hand screws



Automatic display pivot function at the wall-mount



Specification	
Print method	Direct thermal line
Print width	64/76mm
Dot density	512/576dot/line
Interface	Serial+USB, ethernet port optional
Paper diameter	80mm
Line space	3.75mm(can be adjustable)
Character Size	ANK Font Font A: 12×24dots Font B: 9×17dots
Code page	Simplified/Traditional Chinese Character: 24×24dots PC437/Katakana/PC850/PC860/PC863/PC865/West Europe/Greek/Hebrew/East Europe/Iran/WPC1252/PC866/PC852/PC858/IranII/Latvian/Arabic/PT151,1251/PC737/WPC/1257/Thai Vietnam/PC864/PC1001/(Latvian)/(PC1001)/(PT151,1251)/(WPC1257)/(PC864)/(Vietnam)/(Thai)
Fonts	GB18030
Data	128K bytes
NV Flash	256K bytes
Cashdrawer out	DC 24V/1A
Power supply	AC 110V/220V, 50 ~ 60Hz, DC 24V/2.5A
Auto Cutter	1 million