EB-2255U



DATASHEET / BROCHURE



















Full HD, dynamic projector with 3LCD technology, with wireless LAN connectivity and flexible, easy-to-use features.

Deliver Full HD presentations to bring sharp images and bright colours to any meeting room with our super-bright business projector. The EB-2255U is designed to project a scalable image up to a massive 300 inches, and offers a range of connectivity options including screen mirroring and Wireless LAN connectivity.

Outstanding quality display of up to 300 inches

Full HD resolution combined with Epson's 3LCD technology ensures high-quality content has more vivid colours and brighter images. HDMI connectivity guarantees sharper and clearer presentations delivered on a scalable image size of up to 300 inches.

Simple setup and multiple connectivity

The EB-2255U offers a wide range of connectivity options, including screen mirroring, wireless LAN and two HDMI inputs. Setup is easy too, thanks to features including auto-power-on, focus help, keystone correction and screen fit - delivering presentations quickly and efficiently.

Highly reliable

Project for longer with improved reliability and a longer lamp life of up to 10,000 hours in eco mode.

Home screen

The home screen offers quick and easy access to a variety of useful functions, such as connection sources. Wireless connections can also be made easily using the information on the screen.

Gesture Presenter

Change slides by simply moving your hand, making even smarter presentations a reality by liberating the user from their remote control or mouse.

Value-added flexibility

The Multi-PC projection software bundled with the EB-2255U makes it possible to connect up to 50 computers and partition the screen for split screen projection capability - offering far better cost-effectiveness and flexibility than a flat-panel display.

KEY FEATURES

- Up to 300-inch display & great quality
 Full HD resolution with Epson's 3LCD technology
- Bring presentations to life
 Outstanding 5,000-lumen brightness
- Extensive connectivity options
 Including screen mirroring and wireless LAN, as well as dual HDMI
- Flexible interaction
 Split-screen and multi-PC projection
- Gesture Presenter
 Intuitively use gestures to control the projector

Authorized Distributor & Service Provider:



UAN: 021-111-633-675

Web: www.nedogroup.com





PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.76 inch with D10

IMAGE

Color Light Output 5,000 Lumen- 3,800 Lumen (economy) In accordance with IDMS15.4

White Light Output 5,000 Lumen - 3,800 Lumen (economy) In accordance with ISO 21118:2012

Resolution WUXGA, 1920 x 1200, 16:10

 High Definition
 Full HD

 Aspect Ratio
 16:10

 Contrast Ratio
 15,000 : 1

 Light source
 Lamp

Lamp 300 W, 5,000 h durability, 10,000 h durability (economy mode)

Keystone Correction Auto vertical: \pm 30 °, Auto horizontal \pm 20 °

Colour Video Processing 10 Bits
2D Vertical Refresh Rate 200 Hz - 240 Hz
Colour Reproduction Upto 1.07 billion colours

OPTICAL

 Throw Ratio
 1.38 - 2.28:1

 Zoom
 Manual, Factor: 1 - 1.6

Lens Optical

Screen Size 50 inches - 300 inches
Projection Distance Wide 1.5 m (50 inch screen
Projection Distance Tele 9 m (300 inch screen

Projection Lens F Number 1.5 - 2
Projection Lens Focal Length 23 mm - 38.4 mm
Projection Lens Focus Manual
Offset 10 : 1

CONNECTIVITY

USB Display Function 3 in 1: Image / Mouse / Sound

Interfaces USB 2.0 Type A, USB 2.0 Type B, RS-232C, Ethernet interface (100 Base-TX / 10 Base-T),

Gigabit ethernet interface, VGA in (2x), VGA out, HDMI in (2x), Composite in, RGB in (2x), RGB out, MHL, Stereo mini jack audio out, Stereo mini jack audio in (2x), Miracast, Wireless LAN

b/g/n (2.4GHz), Wireless LAN IEEE 802.11a/b/g/n/ac

Epson iProjection App Ad-Hoc / Infrastructure

ADVANCED FEATURES

Security Kensington lock, Security bar, Control panel lock, Password lock, Padlock, Wireless LAN unit

lock, Wireless LAN security, Password protection

2D Colour Modes Dynamic, Cinema, Presentation, sRGB, Blackboard, DICOM SIM

Other features AV Mute Slide, Auto Power On, Automatic input selection, Automatic keystone correction,

Built-in speaker, CEC compatible, Direct Power on/off, Document Camera Compatible, Fit to Screen, Freeze image, Home Screen, JPEG Viewer, Long lamp life, Network administration, OSD copy function, PC Free, Projection App for Chromebook, Quick Corner, Screen Mirroring,

Slide show, Split-Screen-Function, Wireless LAN capable, iProjection App

Video Color Modes Blackboard, Dynamic, Photo, Presentation, sRGB, DICOM SIM

Projector control via: AMX, Crestron, Control4

EB-2255U

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- User Manual (CD-ROM)
- Warranty card
- Wireless LAN unit
- Main unit

<u>Authorized Distributor & Service Provider:</u>



UAN: 021-111-633-675

Web: www.nedogroup.com





PRODUCT SPECIFICATIONS

GENERAL

Power consumption 405 Watt, 323 Watt (economy), 0.5 Watt (standby)

Supply Voltage AC 220 V - 240 V, 50 Hz - 60 Hz

Product dimensions 377 x 291 x 110 mm (Width x Depth x Height)

Product weight 4.7 kg

Noise Level Normal: 39 dB (A) - Economy: 29 dB (A) Supported Temperature Operation 5° C - 40° C, Storage - 10° C - 60° C Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance.

Included Software EasyMP Monitor, iProjection

Options Soft carry case Loudspeaker 16 Watt

Room Type / Application Boardroom, Large Meeting Room / Auditorium

Positioning Ceiling Mounted, Desktop

Colour White

OTHER

Warranty 60 months Carry in or 8,000 h, Lamp: 60 months or 1,000 h

Optional warranty extension available

EB-2255U

WHAT'S IN THE BOX

- Computer cable
- Power cable
- Remote control incl. batteries
- Software (CD)
- User Manual (CD-ROM)
- Warranty card
- Wireless LAN unit
- Main unit

Authorized Distributor & Service Provider:



UAN: 021-111-633-675

Web: www.nedogroup.com



OPTIONAL ACCESSORIES

- Air Filter ELPAF41 V13H134A41
- Wireless LAN Adapter ELPAP10 V12H731P01
- Soft Carry Case ELPKS68 V12H001K68
- Ceiling Mount (White) ELPMB23 V12H003B23
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14
- FI PI P95 V13H010L95
- Control and Connection Box ELPCB02 V12H614040
- Control and Connection Box ELPCB03 V12H927040

EB-2255U

Authorized Distributor & Service Provider:



UAN: 021-111-633-675

Web: www.nedogroup.com

LOGISTICS INFORMATION

SKU	V11H815040 V11H815041
EAN code	8715946628486
Country of Origin	China
Layer	4 Units





^{*} Warranty offers are not available for all countries. Please contact your local Epson representative.

For further information please contact your local Epson office or visit www.epson-europe.com

Austria 01 253 49 78 333 Belgium +32 (0)2 792 04 47 Czech 800/142 052 Denmark 44 50 85 85 Finland 0201 552 091 France 09

(Cost of local call, operator charges may apply) Germany +49 (0) 2159/92 79 500 Greece +30 211 198 62 12 Hungary 06800 147 83 Ireland 01 436 7742 Italy 02-660321 10 (0,12 /min) Luxembourg +352 27860692 Middle East +9714 8872172 Netherlands +31 (0)20 708 5099 Norway

+47 67 11 37 00 Poland 0-0-800 4911299 (0,16 zł/min) Portugal 707 222 111 Russia (095) 777-03-55 Slovakia 0850 111 429 South Africa (+2711)

Spain 93 582 15 00 Sweden 0771-400135 (Mobilsamtal - 0,99 kr/min, Lokala samtal - 0,30 kr/min, Utlandssamtal - 0,89 kr/min) Switzerland 022 592 7923
Turkey (0212) 3360303 United Kingdom 0871 222 6702

1. - iProjection App available on Android and iOS devices.

